

1855A Coax - Precision Video Cable for Analog and Digital



For more information please
call

1-800-Belden1

See Put-ups and Colors

Description:

23 AWG solid .023" bare copper conductor, gas-injected foam HDPE insulation, Duofoil® and a 95% tinned copper braid shield, PVC jacket.

PHYSICAL CHARACTERISTICS:

CONDUCTOR:

Number of Coax	1
Total Number of Conductors	1
RG Type	Sub-miniature 59/U
AWG	23
Stranding	Solid
Conductor Diameter	.0227 in.
Conductor Material	BC - Bare Copper

INSULATION:

Insulation Material	Gas-injected FHDPE - Foam High Density Polyethylene
Insulation Diameter	.102 in.

OUTER SHIELD:

Outer Shield Material Trade Name	Duofoil®
Outer Shield Type	Tape/Braid

Outer Shield Material :

Layer Number	Trade Name	Type	Material	% Coverage (%)
1	Duofoil®	Tape	Aluminum Foil-Polyester Tape-Aluminum Foil	100
2		Braid	TC - Tinned Copper	95

Outer Shield %Coverage	100 %
------------------------	-------

OUTER JACKET:

Outer Jacket Material	PVC - Polyvinyl Chloride
-----------------------	--------------------------

OVERALL NOMINAL DIAMETER:

Overall Nominal Diameter	.159 in.
--------------------------	----------

MECHANICAL CHARACTERISTICS:

Operating Temperature Range	-30°C To +75°C
UL Temperature Rating	75°C

1855A Coax - Precision Video Cable for Analog and Digital

Bulk Cable Weight	18 lbs/1000 ft.
Max. Recommended Pulling Tension	36 lbs.
Min. Bend Radius (Install)	1.5 in.

APPLICABLE SPECIFICATIONS AND AGENCY COMPLIANCE:

APPLICABLE STANDARDS:

NEC/(UL) Specification	CMR
CEC/C(UL) Specification	CMG

FLAME TEST:

UL Flame Test	UL1666 Riser
CSA Flame Test	FT4

SUITABILITY:

Suitability - Indoor	Yes
Suitability - Outdoor	Yes - Black only
Suitability - Aerial	Yes - Black only
Suggested Connectors	BNC - Kings 2065-11-9

PLENUM/NON-PLENUM:

Plenum (Y/N)	N
--------------	---

ELECTRICAL CHARACTERISTICS:

Nom. Characteristic Impedance	75 +/- 1.5 Ohms
Nom. Inductance	.106 µH/ft
Nom. Capacitance Conductor to Shield	16.5 pF/ft
Nominal Velocity of Propagation	83 %
Nominal Delay	1.24 ns/ft
Nom. Conductor DC Resistance @ 20 Deg. C	20.1 Ohms/1000 ft
Nominal Outer Shield DC Resistance	7.6 Ohms/1000 ft

Minimum Return Loss :

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Minimum Return Loss (dB)
		5	850	23
		851	3000	21

Nom. Attenuation :



1855A Coax - Precision Video Cable for Analog and Digital

Description	Frequency (MHz)	Start Frequency (MHz)	Stop Frequency (MHz)	Nom. Attenuation (dB/100 ft.)
	1			.39
	3.58			.78
	5			.92
	7			1.08
	10			1.20
	67.5			2.83
	71.5			3.06
	88.5			3.16
	100			3.33
	135			3.81
	143			3.92
	180			4.38
	270			5.40
	360			6.20
	540			7.70
	720			9.47
	750			9.59
	1000			10.5
	1500			13.0
	2000			15.1
	2250			16.0
	3000			18.5

Max. Operating Voltage - UL

300 V RMS

NOTES:

Notes

All performance data contained herein are calculated based on nominal dimensions and material properties. Actual performance may vary. Impedance tested in accordance with ASTM D-4566 paragraph 43.2, option 2 using a 75 Ohm fixed bridge and termination. Return loss tested in accordance with ASTM D-4566 paragraph 45.3 using a 75 Ohm fixed bridge and termination. Also available in multiples, bundled. See 7787A through 7792A. 100% Sweep tested 5 MHz to 3 GHz. SDI/HDTV Digital Video.

PUT-UPS AND COLORS:

Item	Description	Put-Up (ft.)	Ship Weight (lbs.)	Jacket Color	Notes
1855A 0011000	#23 PE/GIFHDPE SH FR PVC	1000	18	BROWN	C
1855A 0021000	#23 PE/GIFHDPE SH FR PVC	1000	18	RED	C
1855A 0031000	#23 PE/GIFHDPE SH FR PVC	1000	18	ORANGE	C
1855A 0041000	#23 PE/GIFHDPE SH FR PVC	1000	18	YELLOW	C
1855A 0061000	#23 PE/GIFHDPE SH FR PVC	1000	18	BLUE, LIGHT	C
1855A 0071000	#23 PE/GIFHDPE SH FR PVC	1000	18	VIOLET	C



1855A Coax - Precision Video Cable for Analog and Digital

1855A 0081000	#23 PE/GIFHDPE SH FR PVC	1000	18	GRAY	C
1855A 0091000	#23 PE/GIFHDPE SH FR PVC	1000	18	WHITE	C
1855A 0101000	#23 PE/GIFHDPE SH FR PVC	1000	18	BLACK	C
1855A 010500	#23 PE/GIFHDPE SH FR PVC	500	9	BLACK	
1855A N3U1000	#23 PE/GIFHDPE SH FR PVC	1000	18	GREEN, MIL	C

C = CRATE REEL PUT-UP.

Revision Number: 1 Revision Date: 02-19-2004

© 2003 Belden Wire & Cable Company
All Rights Reserved.

Although Belden Electronics Division ("Belden") makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.